

By Matthijs Alles - (c)2009 Bixie
Adapted from the original VirtueUpload 1.0 from Tobias Kuhn.
Based on J1.5 component SimpleCalendar from Fabrizio Albonico.

For Joomla! 1.5 and VirtueMart 1.1.3 or 1.1.4

More info and support: www.bixie.nl/forum

INSTALLATION:

Install the component com_virtueupload.zip and the module mod_virtueupload.zip in the backend of Joomla (Extensions->Install/Uninstall).

COMPONENT SETTINGS:

Default settings are:

Setting:	Default:	Description:
Enable uploads	Yes	General on/off toggle.
Upload folder	virtueupload	Default folder is created on component-installation. Make sure it's writable!
Banned extensions	.php .exe .com .bat .ini .js .htm .html	Ban these extensions when uploaded.
Max. uploadsize	8024000	Maximum uploadsize in bytes. Remember to change your PHP-settings accordingly.
VM Product attribute	Upload	Name of the attribute added to the VirtueMart-product. Case-sensitive!
Administrator mail	0	If an email-address is entered, a mail will be sent when a upload is done. 0 switches mail off.
Ban IP-addresses	0	The number of tries allowed before an IP address is banned. 0 switches it off.
Show thumbnail	Yes	Shows a thumbnail or icon with the upload-information and mail.
Icon width	64px	Width of the icon.
Icon height	64px	Height of the icon.
Thumbnail width	125px	Width of the thumbnail.
Thumbnail height	125px	Height of the thumbnail.

MODULE SETTINGS:

Set module position to “upload”. You can type this value in the pulldown-menu (yes, you can!)

Details

Module Type:	mod_virtueupload
Title:	VirtueUpload Module
Show Title:	<input type="radio"/> No <input checked="" type="radio"/> Yes
Enabled:	<input type="radio"/> No <input checked="" type="radio"/> Yes
Position:	upload
Order:	0::VirtueUpload Module
Access Level:	Public Registered Special
ID:	23
Description:	<p>Module voor VirtueUpload. Te plaatsen in de flypage. Include with {loadposition positionname} in product description.</p>

Menu Assignment

Menus: All None Select Menu Item(s) from the List

You can use another position, but then make sure to adjust your settings below accordingly.

VIRTUEMART SETTINGS:

These settings are done in the backend-section of the VirtueMart component. Add these settings to each product you want to attach an upload to.

In **product edit**:

-Add to the **Product Description** the following tag anywhere in your text:

```
{loadposition upload}
```

If the module is published in a different position than ‘upload’, change it here.

-Add an “**Custom Attribute**” with the name “Upload”.

This is done in ‘Custom Attribute List’ on the tab ‘Product status’. You can use a different name, but you must change the setting in the VirtueUpload component Settings accordingly.

Attention:

-Module mod_virtueupload must be published in position “upload”.

-The option **Enable content mambots / plugins in descriptions?** in the Global VirtueMart config must be checked.

VIRTUEMART FILE-HACKS:

Overwriting files

The adjusted files for the default VirtueMart 1.1.3 and 1.1.4 installation are included in the com_virtueupload.zip file. They are in the folder 'vm-hacks' in components/com_virtueupload/assets.

This is essentially an update patch for VirtueMart. Make sure you use the right files for your VirtueMart version! Copy the files from your local PC to the root of your site. You'll be prompted to overwrite a file 5 times. If done so, your VirtueMart is successfully adjusted vor VirtueUpload.

Attention:

-There are separate files for VirtueMart 1.1.3 and VirtueMart 1.1.4! Make sure you use the right ones!

-This only works on a standard VirtueMart 1.1.3 or 1.1.4 installation in default-theme. If you use an customized VirtueMart or custom theme, use the manual adjustments described below.

-Always make a backup before overwriting your files!

-For VirtueMart 1.1.4 the [Make custom attributes optional-hack](#) must be applied. The adjusted ps_cart file is included in the hack files.

Manual adjustments

Five files must be changed:

-In folder components/com_virtuemart/themes/yourthemename/templates

- /basket/basket_b2c.html.php
- /basket/ro_basket_b2c.html.php
- /pages/account.order_details.php

```
if (file_exists
(JPATH_ADMINISTRATOR.DS."components".DS."com_virtueupload".DS."classes".DS."output.class.php")) {
require_once (JPATH_ADMINISTRATOR.DS."components".DS."com_virtueupload".DS."classes".DS."output.class.php");
}
```

- /order_emails/confirmation_email.tpl.php

-In folder administrator/components

- /com_virtuemart/classes/ps_checkout.php

Place on top of each file that you change, just below _JEXEC check:

Templatefiles

- In *basket/basket_b2c.html.php* (line 33) and *basket/ro_basket_b2c.html.php* (line 36) (same for vm1.1.3 and vm1.1.4):
Replace line:

```
<td><?php echo $product['product_name'] . $product['product_attributes' ?></td>
```

With:

```
<td><?php echo $product['product_name'].$product['product_attributes'].  
VUOutput::UploadInfo ( $product['product_name'] , 'cart' ) ?></td>
```

- In *pages/account.order_details.php*
- Starting from line 361 you see (same for vm1.1.3 and vm1.1.4)::

```
// ***** Change guard to use new flag $link_to_product instead of !empty( $product_id )  
        if( $link_to_product) {  
            echo '<a href="'. $sess->url(  
$mm_action_url."index.php?page=shop.product_details&product_id=$product_id") .'" title="'. $dbcart->  
>f("order_item_name").'">';  
        }  
        $dbcart->p("order_item_name");  
        echo " <div style=\"font-size:smaller;\">" . $dbcart->  
>f("product_attribute") . "</div>";  
// ***** Change guard to use new flag $link_to_product instead of !empty( $product_id )  
        if( $link_to_product) {  
            echo "</a>";  
        }
```

Replace that bit with:

```
// ***** Change guard to use new flag $link_to_product instead of !empty( $product_id )  
        if( $link_to_product) {  
            $senda = "</a>";  
        }  
        if( $link_to_product) {  
echo '<a href="'. $sess->url( $mm_action_url."index.php?page=shop.product_details&product_id=$product_id") .'  
" title="'. $dbcart->f("order_item_name").'">';  
        }  
        $dbcart->p("order_item_name");  
echo $senda." <div style=\"font-size:smaller;\">" . $dbcart->f("product_attribute").  
VUOutput::UploadInfo ( $dbcart->f("product_attribute") , 'cart' ) . "</div>";  
// ***** Change guard to use new flag $link_to_product instead of !empty( $product_id )
```

- In `order_emails/confirmation_email.tpl.php` regel 184 (same for vm1.1.3 and vm1.1.4). Replace line:

```
<td><?php $dboi->p("product_name")?>
<?php echo ($dboi->f("product_attribute") ? ' ('.$dboi->f("product_attribute").')' : ''); ?></td>
```

With:

```
<td><?php $dboi->p("product_name")?>
<?php echo ($dboi->f("product_attribute") ? ' ('.$dboi->f("product_attribute").')' : ''); ?>
<?php echo VUOutput::UploadInfo ( $dboi->f("product_attribute") , 'cart' ); ?></td>
```

VirtueMart Core-bestanden

To be able to add an order ID to the upload when the product is ordered, you must hack one VirtueMart core file. Remember that this will be lost when you update VirtueMart.

- In `administrator/components/com_virtuemart/classes/ps_checkout.php`, line 1101 (same for vm1.1.3 and vm1.1.4):

Just below this line:

```
$description .= $ps_product->getDescriptionWithTax($_SESSION['cart'][$i]["description"],
$dboi->f('product_id'));
```

Add this line:

```
VUOutput::AddOrderid( $description , $order_id );
```